



## TECHNICAL BULLETIN

### PRODUCT #925 CLEAR SKYLIGHT COATING

FLUID APPLIED REINFORCED ROOFING • REFLECTIVE COATING SYSTEMS

#### DESCRIPTION

**Product No. 925 Clear Skylight Coating** is a water based, clear, acrylic coating. It is formulated with premium acrylic resin, to form a hard, long lasting, clear surface on aged and worn fiberglass skylights. When applied properly it will give worn fiberglass skylights additional years of useful life. **Clear Skylight Coating** may also be used as a clear sealer on other surfaces such as wood and masonry.

#### PHYSICAL PROPERTIES

Color..... Clear when dry  
Total Solids..... 45-55% by weight  
Consistency..... Light, Roll Brush or Spray  
Appearance..... Wet – Milky Liquid  
Weatherability..... Excellent  
Application Rate..... 1 - 1½ Gal. per 100 sq. ft.  
Application Temperature..... Minimum 60° F  
Dry Time (through dehydration)..... 1 hr. @ 75° F  
Tack free time..... 30 Min.

#### PREPARATION

Surface must be dry and free of dirt, dust, oil, grease, wax, rust, chalky or loose paint, mildew and any other surface contamination that may inhibit adhesion. Repair any splits or holes using proper sealing compound.

#### APPLICATION

Using roller, brush or spray equipment, apply to the properly prepared surface at the rate of 1 to 1½ gallons per 100 sq. ft.. Severely weathered skylights may require one or more additional coats. Wait 30 minutes to 1 hour between coats.

Wet material and all tools and equipment may be cleaned with water. Rinse tools and equipment with water before using. Mix thoroughly before using. Do not dilute.

**PRECAUTIONS:** Do not apply **Clear Skylight Coating** when surface or air temperature is below 60° F, or if cold weather, rain or fog is expected within twenty-four hours of application. **Clear Skylight Coating** cures through dehydration. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement. Not intended for use on Acrylic or Plexiglass skylights.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING. NOT DOT REGULATED  
STORE CONTAINERS IN COOL, DRY, PROTECTED AREA. KEEP FROM FREEZING

---

#### LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown hereon. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.

---

TEC925 0417C