



TECHNICAL BULLETIN

“POLY OIL SIL” Oil Spot Primer WCP #601

FLUID APPLIED REINFORCED ROOFING • REFLECTIVE COATING SYSTEMS

1.0 DESCRIPTION AND RECOMMENDED USE

POLY OIL SIL (WCP #601) is an acrylic emulsion used to promote adhesion over gasoline, grease and oil spots or chemical stains prior to the application of coal tar or asphalt base sealcoat on asphaltic surfaces. It is easy to use on parking lots, driveways, airport runways, traffic safety islands or any asphalt surface.

2.0 PHYSICAL PROPERTIES

Color	Milky Liquid - Dries Clear
Solids Content	50+% (by weight)
Weight per Gallon	9.5 to 10.5 lbs.
Flammability (wet)	Non-flammable

3.0 GUIDE to SURFACE PREPARATION and APPLICATION

Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease or any other chemical stain spots.

Mix well before using. Use full strength on heavy spots. Reduce 1 to 1 with water, depending on the build-up of the oil, grease or any other chemical stain spots. Sprinkle a slight amount of silica sand on POLY OIL SIL to improve adhesion of the sealcoat.

3.1 SUGGESTED RATES (approximate)

Approximately .10 (1/10) undiluted gallon per square yard to be primed.

4.0 DRYING TIME

At 70 degrees Fahrenheit, and 50% relative humidity, approximately 2 to 3 hours. Drying time is dependent on temperature, direct sunlight, humidity, air movement and thickness of application.

5.0 CLEAN UP

Use clean water before product has dried. Wash tools in water. Dried product may be removed using solvent or paint remover.

6.0 PRECAUTIONS

Keep from freezing. Do not store in direct sunlight. Container should be closed when not in use. Keep out of reach of children. If spilled or splashed on skin, wash immediately with water. Refer to MSDS (available upon request).

7.0 SHELF-LIFE

Up to one-year minimum in unopened container.

8.0 AVAILABILITY

5 Gallon Pails
55 Gallon Drum

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with Western Colloid instructions. Western Colloid does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at Western Colloid's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Western Colloid in writing at the addresses shown herein. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES OR LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE.

601_0104a