



TECHNICAL BULLETIN

“FLEX CRAC” Cold Pour Crack Filler WCP #651

FLUID APPLIED REINFORCED ROOFING • REFLECTIVE COATING SYSTEMS

1.0 DESCRIPTION AND RECOMMENDED USE

FLEX-CRAC COLD POUR (WCP #651) is a rubberized asphalt emulsion with greater flexibility designed for filling narrow pavement cracks up to 1/2" in width, in asphaltic, as well as, concrete surfaces. It has resilient characteristics that can allow a threading quality or memory. It has excellent flow properties and no pinholing. It is ready to use on parking lots, airports, athletic courts, driveways, traffic safety islands, playgrounds and walkways.

1.1 MATERIAL SPECIFICATIONS

FLEX-CRAC COLD POUR (WCP #651) meets emulsified asphalts - **AASHTO Designation M 140-70 - ASTM D 977-73 and D-244 Testing Emulsified Asphalts.**

2.0 SURFACE PREPARATION

Surface must be dry, clean, and free from all loose material, dirt and dust. Fill cracks exceeding 1/2" (width up to 1") with A/C Leveling Compound (WCP #653). Oil contaminated cracks can be treated with Western Colloid POLY OIL SIL (WCP #601).

3.0 APPLICATION

Mix well before using. Use as is. Pour FLEX-CRAC into cracks completely. Before FLEX-CRAC sets up, scrape excess from surface using a rubber squeegee; allow to cure completely before sealing with a mechanical applicator. FLEX-CRAC will set under good conditions in several hours, depending on weather and filler thickness.

4.0 COVERAGE

Indefinite. For estimation purposes - up to 150 linear feet of 1/2" x 1/4" depth crack per gallon.

5.0 CLEAN UP

Use clean water before product has dried. Wash tools in water. Dried product may be removed using WCP #2000.

6.0 PRECAUTIONS

Do not store in direct sunlight or where temperatures exceed 100 degrees Fahrenheit. Container should be closed when not in use. Keep out of reach of children. Do not use when rain is forecast, on wet surfaces or when asphalt and air temperature is below 55 degrees Fahrenheit. Refer to MSDS (available upon request).

7.0 SHELF-LIFE

Up to six months in unopened container.

8.0 AVAILABILITY

5 Gallon Pails

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with Western Colloid instructions. Western Colloid does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at Western Colloid's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Western Colloid in writing at the addresses shown herein. **THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES OR LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE.**

651_0104a